

Whitehaven Theatre Standard Rig Full Fixture Report

June 2026 McLauchlan Family Auditorium

Fixtures

Channel	Patch	Wayline	Name	Mode	Optics	Filters	Accessories	Location	Focus	Weight	Rating
1	1.11	2/24	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 2	Downstage	8.3kg	800W
2	1.12	B2/23	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 2	Downstage	8.3kg	800W
3	1.15	B2/19	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 2	Downstage	8.3kg	800W
4	1.19		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 2	Downstage	8.3kg	800W
5	1.22	B2/6	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 2	Downstage	8.3kg	800W
6	1.26		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 1	Mid Stage	8.3kg	800W
7	1.27		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 1	Mid Stage	8.3kg	800W
8	1.29		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 1	Mid Stage	8.3kg	800W
9	1.31	B1/17	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 1	Mid Stage	8.3kg	800W
10	1.33		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 1	Mid Stage	8.3kg	800W
11	1.50		Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 2	Up Stage	5kg	1.2KW
12	1.51		Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 2	Up Stage	5kg	1.2KW
13	1.53		Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 2	Up Stage	5kg	1.2KW

14	1.55		Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 2	Up Stage	5kg	1.2KW
15	1.57		Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 2	Up Stage	5kg	1.2KW
31	1.13	B2/21	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 2	Downstage	8.3kg	800W
32	1.17	B2/13	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 2	Downstage	8.3kg	800W
33	1.21	B2/7	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 2	Downstage	8.3kg	800W
34	1.24	B2/2	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 2	Downstage	8.3kg	800W
35	1.25	B2/1	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 2	Downstage	8.3kg	800W
36	1.28		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 1	Mid Stage	8.3kg	800W
37	1.30	B1/19	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 1	Mid Stage	8.3kg	800W
38	1.32		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053		Bridge 1	Mid Stage	8.3kg	800W
39	1.34		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 1	Mid Stage	8.3kg	800W
40	1.35		Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 1	Mid Stage	8.3kg	800W
41	1.52		Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 2	Up Stage	5kg	1.2KW
42	1.54		Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 2	Up Stage	5kg	1.2KW
43	1.56		Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 2	Up Stage	5kg	1.2KW

44	1.58	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 2	Up Stage	5kg	1.2KW
45	1.59	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 2	Up Stage	5kg	1.2KW
51	1.38	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 1		5kg	1.2KW
52	1.39	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 1		5kg	1.2KW
53	1.40	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 1		5kg	1.2KW
54	1.62	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 3		5kg	1.2KW
55	1.63	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 3		5kg	1.2KW
56	1.64	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 3		5kg	1.2KW
57	1.74	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 4		5kg	1.2KW
58	1.75	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 4		5kg	1.2KW
59	1.76	Selecon 1200 High Performance Fresnel	Control	13° - 66°	E154	Barndoors	LX 4		5kg	1.2KW
61	1.41	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 1		5kg	1.2KW
62	1.42	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 1		5kg	1.2KW

63	1.43	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 1		5kg	1.2KW
64	1.65	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 3		5kg	1.2KW
65	1.66	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 3		5kg	1.2KW
66	1.67	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 3		5kg	1.2KW
67	1.77	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 4		5kg	1.2KW
68	1.78	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 4		5kg	1.2KW
69	1.79	Selecon 1200 High Performance Fresnel	Control	13° - 66°	R053	Barndoors	LX 4		5kg	1.2KW
81	1.1	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 3	Thrust	8.3kg	800W
82	1.2	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 3	Thrust	8.3kg	800W
83	1.4	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 3	Thrust	8.3kg	800W
84	1.6	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 3	Thrust	8.3kg	800W
85	1.8	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	E154, R119		Bridge 3	Thrust	8.3kg	800W
86	1.3	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 3	Thrust	8.3kg	800W
87	1.5	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 3	Thrust	8.3kg	800W
88	1.7	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119		Bridge 3	Thrust	8.3kg	800W

89	1.9	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119	Bridge 3	Thrust	8.3kg	800W
90	1.10	Selecon SPX 15°-35° Zoomspot	Control	15° - 35°	R053, R119	Bridge 3	Thrust	8.3kg	800W
101	2.1	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 1		15kg	500W
102	2.14	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 1		15kg	500W
103	2.27	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 1		15kg	500W
104	2.40	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 1		15kg	500W
105	2.53	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 1		15kg	500W
106	2.66	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 2		15kg	500W
107	2.79	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 2		15kg	500W
108	2.92	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 2		15kg	500W
109	2.105	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 2		15kg	500W
110	2.118	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 2		15kg	500W
111	2.131	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 3		15kg	500W
112	2.144	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 3		15kg	500W
113	2.157	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 3		15kg	500W
114	2.170	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 3		15kg	500W
115	2.183	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°		LX 3		15kg	500W

116	2.196	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°	LX 4		15kg	500W
117	2.209	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°	LX 4		15kg	500W
118	2.222	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°	LX 4		15kg	500W
119	2.235	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°	LX 4		15kg	500W
120	2.248	Vello Light LED XP-700 Zoom	Reduced Mode	8° - 60°	LX 4		15kg	500W
181	1.49	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 2	DS Gobo Wash	9.5kg	1kW
182	1.60	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 2	DS Gobo Wash	9.5kg	1kW
183	1.61	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 3	Mid Gobo Wash	9.5kg	1kW
184	1.68	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 3	Mid Gobo Wash	9.5kg	1kW
185	1.73	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 4	US Gobo Wash	9.5kg	1kW
186	1.80	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	LX 4	US Gobo Wash	9.5kg	1kW
200	1.14	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	Bridge 2	FOH Specials	9.5kg	1kW
201	1.16	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	Bridge 2	FOH Specials	9.5kg	1kW
202	1.18	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	Bridge 2	FOH Specials	9.5kg	1kW

203	1.20	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	Bridge 2	FOH Specials	9.5kg	1kW
204	1.23	Selecon Pacific 12°-28° Zoomspot	Control	240V BP	Bridge 2	FOH Specials	9.5kg	1kW
251	1.356	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
252	1.365	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
253	1.374	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
254	1.383	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
255	1.392	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
256	1.401	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
257	1.410	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
258	1.419	Vello Light LED Stage Bar1251 RGBWA	A	45°	LX 5	Cyc	11kg	400W
259	1.428	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
260	1.437	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
261	1.446	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W

262	1.455	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
263	1.464	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
264	1.473	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
265	1.482	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
266	1.491	Vello Light LED Stage Bar1251 RGBWA	A	45°	Ground Row	Cyc	11kg	400W
301	1.198	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	Advanced Truss		22kg	450W
302	1.219	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	Advanced Truss		22kg	450W
303	1.240	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	Advanced Truss		22kg	450W
304	1.261	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	Advanced Truss		22kg	450W
305	2.261	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 1		22kg	450W
306	2.282	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 1		22kg	450W
307	2.303	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 3		22kg	450W
308	2.324	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 3		22kg	450W
309	2.345	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 4		22kg	450W
310	2.366	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°	LX 4		22kg	450W

311	2.387	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°		LX 4		22kg	450W
312	2.408	Vello Light LED Spot 330 CMY	Reduced Mode	7° - 31°		LX 4		22kg	450W
501	1.110	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		OP Pan		8.2kg	300W
502	1.121	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		OP Pan		8.2kg	300W
503	1.132	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		OP Pan		8.2kg	300W
504	1.143	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		OP Pan		8.2kg	300W
506	1.154	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		PS Pan		8.2kg	300W
507	1.165	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		PS Pan		8.2kg	300W
508	1.176	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		PS Pan		8.2kg	300W
509	1.187	Vello Light LED XP-300 Zoom	Reduced 1 05.14	5° - 60°		PS Pan		8.2kg	300W
								1299.1kg	92.8KW